

VÁLVULA DOBLE SIFÓN | BONDE À DOUBLE SIPHON DOUBLE SIPHON DRAIN | VALVOLA A DOPPIO SIFONE | DOPPELSIPHON-ABLAUF

ES | **FILTRO CABELLO**
 FR | PANIER POUR CHEVEUX
 EN | HAIR FILTER
 IT | FILTRO CAPELLI
 DK | HAARFILTER



ES | **VASO SIFÓNICO**
 FR | SIPHON
 EN | SIPHONIC CUP
 IT | SIFONE
 DK | SIPHONBECHER



ES | **TORNILLOS INOXIDABLES**
 FR | VIS ACIER INOXYDABLE
 EN | STAINLESS STEEL SCREWS
 IT | VITI IN ACCIAIO INOSSIDABILE
 DK | ROSTFREIE SCHRAUBEN



ES | **BRIDA DE PVC**
 FR | BRIDE EN PVC
 EN | PVC FLANGE
 IT | FLANGIA IN PVC
 DK | FLANSCH AUS PVC



ES | **JUNTA DE CAUCHO**
 FR | CONSEIL EN CAOUTCHOUC
 EN | RUBBER BOARD
 IT | SCHEDA DI GOMMA
 DK | GUMMI-DICHTUNG



ES | **CUERPO VÁLVULA**
 FR | CORPS DE BONDE
 EN | DRAINS BODY
 IT | CORPO VALVOLA
 DK | VENTILGEHÄUSE



ES | **TUERCA Y JUNTA**
 FR | ECROU ET JOINT
 EN | NUT AND GASKET
 IT | DADO E GUARNIZIONE
 DK | MUTTER UND DICHTUNG



CAUDAL | DÉBIT | FLOW | FLUSSO | DURCHFLOSSMENGE

ES | **CON 15 MM DE AGUA: 60L/MIN**
 FR | AVEC 15 MM. D'EAU: 60L/MIN
 EN | WITH 15 MM. WATER: 60L/MIN
 IT | CON 15 MM. DI ACQUA: 60L/MIN
 DK | BEI 15 MM WASSER: 60L/MIN

TEMP. MAX. 100°C

CE

EN 1253-1:2014

EN 1253-2:2014

